

# DEEPER INTELLIGENCE BEYOND THE EDGE



DeepinView

Hikvision's DeepinView 71xx Series Indoor/Outdoor Compact Dome Cameras feature our state-of-the-art video analytics fueled by Artificial Intelligence (AI). These cameras bring AI edge computing to life, enabling automated detection, categorization, and analysis of objects in view with unparalleled accuracy and efficiency. DeepinView cameras offer video and image data paired with the intelligent insights you need for better security and business intelligence.

## HIGHLIGHTS

### ▣ MULTIPLE, FLEXIBLE AI APPLICATIONS



Perimeter Protection



Multi-Target-Type Recognition



Queue Management



On/Off Duty Detection



Regional People Counting



Heat Map

### ▣ EXCELLENT PERFORMANCE 24/7



DarkFighter



ePTZ



P-Iris



140 dB WDR



Rich Interfaces

### ▣ BUILT-IN WATERPROOF SPEAKER



Sealing ring and plug at the cavity closure

Waterproof speaker

An independent cavity for speaker

### ▣ ENVIRONMENTALLY CONSCIOUS

Eliminates hazardous plastics as DeepinView Series Cameras are completely PVC-free

### ▣ HIGH SECURITY LEVELS

#### 802.1x EAP-TLS 1.2

To prevent unauthorized device access

#### SFTP

To support safe image transmission between cameras and FTP servers

#### Security Audit Log

To record all data activities to ensure all security operations can be queried

#### Stream Encryption

Stream encryption by RTSP/ RTP over HTTPs

#### Security Chip

The chip supports security boot, software, and firmware signatures

#### Session Timeout

Webpage will return to the login page when activity has paused for a while

## APPLICATION



Retail Stores



Banks & Financial Institutions



Businesses

## WORKING DIAGRAM



iDS-2CD71xx  
FW 5.8.10





I/M NVRs: Records / Alarm  
DeepinMind: Target Search  
FW4.6.0



HikCentral  
Pro 2.3

## PRODUCT SHOWCASE

	
<b>iDS-2CD7146G0-IZS (D)</b>	<b>iDS-2CD7186G0-IZS (D)</b>
4 MP	8 MP
2.8-12mm & 8-32mm	2.8-12mm & 8-32mm
<ul style="list-style-type: none"> <li>• 4 MP @ 60 fps</li> <li>• -40°C/-40F to 60 °C/140F</li> <li>• Built-in Dual-Mic &amp; Speaker</li> <li>• Vibration Detection</li> <li>• Optional Body Heater (-H) and Anti-Corrosion Layer (-Y)</li> </ul>	<ul style="list-style-type: none"> <li>• Supports IP67 &amp; IK10</li> <li>• 12 VDC power output</li> <li>• Support PoE/12 DC /24AC</li> </ul>

# VIDEO, SECURITY & BEYOND

Contact Your Sales Rep:

Phone #:

Email:

General Inquiries/Support: +1 (866) 200-6690 (U.S. and Canada) | +1 (909) 895-0400



For more information, please scan the QR Code.

For more information about this Special Offer, please contact inside sales at [inside.usa@hikvision.com](mailto:inside.usa@hikvision.com), or contact your local Hikvision representative.

©2023 Hikvision USA Inc. and Hikvision Canada Inc. All rights reserved. Hikvision is a registered trademark of Hikvision Digital Technology Co., Ltd. in the US, Canada and other countries. Product specifications and availability are subject to change without notice.

[hikvision.com](http://hikvision.com)

Connect with us:     

**HIKVISION**